

پیشنهاد فنی

تاریخ: ۱۴۰۴/۰۵/۲۷
شماره: Rev ۰۵-۰۸۳۵-۰۳
پیوست: دارد (کاتالوگ)

نام خریدار: شرکت محترم پالایش میعانات گازی آدیش جنوبی
قابل توجه: سرکار خانم مهندس مرادی
عنوان درخواست: ۰۰۱۱

Item	Description				
A	Differential Pressure Gauge Tag No.: as below (SS Tag Plate will be provided as attached picture.) Type: Diaphragm (Elastic element: AISI 316L st.st.) Range: as below , Dual Range (Psi , Bar) Dial Size: 100mm Case Material: Stainless Steel Process Connection: 1/2" NPTM (will be coupled to Manifold: Remote) Precess Connection Material: S.S. 316 Accuracy Class: 1.6 as per EN 837 Protection Degree: IP65 Model: MD15 MFR: NUOVAFIMA				
	Accessories				
	3 Valve Manifold Max Working Pressure: 6000 Psi Material: S.S.316L (NACE MR 0175) Inlet Connection: 1/2" NPTF Outlet Connection: 1/2" NPTF Vent Connection: 1/4" NPTF Model: 3VM01S MFR: VEELOK				
Item	Tag No.	Dial Range	Qty	Delivery	Remark
1	DPI-A	2.5 Bar	1	In Stock	
2	DPI-B	2.5 Bar	1	In Stock	

Item	Description					
B	Pressure Gauge Tag No.: as below (SS Tag Plate will be provided.) Type: Solid Front , Bourdon Tube (seamless tube: AISI 316L st.st) Range: as below Dial Size: 150mm Case Material: Stainless Steel Process Connection: 1/2" NPTM , Bottom Precess Connection Material: S.S. 316 Accuracy Class: 1 as per EN 837-1 Protection Degree: IP65 Model: MGS20 MFR: NUOVAFIMA					
	Item	Tag No.	Range(Bar)	Qty	Delivery	Remark
	1	PI-500	0-100	1	14-16 Working Weeks	
	2	PI-1100	0-100	1		
	3	PI-1300C	0-100	1		

Item	Description						
D	Temperature Gauge Tag No.: as below (SS Tag Plate will be provided as attached picture.) Type: Bi-Metal Range: as below Accuracy Class: 1 as per EN 13190, measuring Range Protection Degree: IP65 Dial Size: 6"(150/160 mm) Dial: Aluminium white with black marking Case: Stainless Steel Process Connection: 1/2" NPTM , Every Angle (Sliding male and swivel nut) Process Connection Material: S.S.316 Stem Diameter: 6 mm Stem Length: 300 mm Stem Material: AISI 316 st. st. Window: Safety Glass Zero-Adjustment: External Zero-Adjustment Screw Model: TB8 MFR: NUOVAFIMA						
	Item	Tag No.	Range (°C)	Stem Diameter (mm)	Stem Length (mm)	Qty	Delivery
	1	TI-1300	0-100	6	300	1	In Stock
	2	TG-505-023	0-100	6	300	1	In Stock
	Remark						

Item	Description						
E	Levelflex Tag No.: as below (SS Tag Plate will be provided as attached picture.) Approval: ATEX II 1/2G Ex ia IIC T6 Ga/Gb Power Supply; Output: 2-wire; 4-20mA HART Display, Operation: SD03 4-line, illum., touch control + data backup function Housing: GT20 dual compartment, Alu, coated Electrical Connection: Gland M20, IP66/68 NEMA4X/6P Probe: as below , rope 4mm, 316, max 150mm nozzle height, center rod Seal: FKM Viton, -30...150oC/-22...302oF Process Connection: NPS 6" Cl.300 RF, 316/316L flange ASME B16.5 Additional Operation Language: English Calibration: 3-point linearity protocol observe minimum probe length, rod/coax >=1000mm, rope >=1250mm Test, Certificate: 3.1 Material certificate, wetted metallic parts, EN10204-3.1 inspection certificate Model: FMP51-BBAECALAA4AUJ+AAF3JAZ1 MFR: E+H						
	Item	Tag No.	Range (mm)	Qty	Delivery	Remark	
	1	LI-523-006	0-4600	1	14-16 Working Weeks	Please specify the exact order code you require	

Item	Description					
F	Pressure Transmitter Tag No.: as below (SS Tag Plate will be provided as attached picture.) Type: Gauge Pressure Transmitter Calibration Range: as below Output Signal: 4 to 20 mA DC Output with Digital Communication (HART 5/HART 7 protocol) Measurement Span (capsule): 0.1 to 10 MPa (14.5 to 1450 psi) (~1.00 to ~99.97 bar) Process Connector Material: 316L S.S. Diaphragm Material: Hastelloy C-276 Amplifier Housing: Cast aluminum alloy Process Connections: 1/2" NPTF Electrical Connection: M20 female, two electrical connections without blind plugs Accuracy Class: $\pm(0.005+0.0035 \text{ URL/ span}) \%$ of Span Integral Indicator: Digital indicator With the Range Setting Switch (Push Button) Mounting Bracket: 316 SST 2-inch Pipe Mounting Approval: IECEx Intrinsically safe and Flameproof Intrinsically safe Ex ia Certificate: IECEx DEK 11.0081X Applicable Standard: IEC 60079-0, IEC 60079-11 Ex ia IIC T4 Ga Enclosure: IP66/IP67 Amb. Temp.: -50 to 60°C (-58 to 140°F), Max. Process Temp.: 120°C (248°F) Electrical Parameters: $U_i=30V$, $I_i=200mA$, $P_i=0.9W$, $C_i=27.6nF$, $L_i=0 \mu H$ Intrinsically safe Ex ic Certificate: IECEx DEK 13.0061X Applicable Standard: IEC 60079-0, IEC 60079-11 Ex ic IIC T4 Gc IP code: IP66 Amb. Temp.: -30 to 60°C (-22 to 140°F) *2, Max. Process Temp.: 120°C (248°F) Electrical Parameters: $U_i=30V$, $C_i=27.6 nF$, $L_i=0 \mu H$ Model: EJA530E-JCS4N-014EL/SU22/YT07/M15/HAC MFR: Yokogawa					
	Accessories Hex Nipple Max Working Pressure: 6000 Psi Material: S.S.316L (NACE MR 0175) Connection: 1/2" NPTM * 1/2" NPTM Model: HN8 MFR: VEELK 2 Valve Manifold Max Working Pressure: 3000 Psi Material: S.S.316L (NACE MR 0175) Inlet Connection: 1/2" NPTF Outlet Connection: 1/2" NPTF Vent Connection: 1/4" NPTF Model: 2VM01S8FF MFR: VEELK					
Item	Tag No.	Calibration Range (Bar)	Instrument Range	Qty	Delivery	Remark
1	PT-521-020	0-30	0.1 to 10 Mpa	1	In Stock	

Item	Description						
G	Pressure Gauge Tag No.: as below (SS Tag Plate will be provided as attached picture.) Type: Diaphragm (Model: MN18) , Bourdon Tube (Model: MGS18) Range: as below Dial Size: 150 mm Case Material: Stainless Steel, Fillable, Filled By Glycerin Process Connection: 1/2" NPTM , Bottom Precess Connection Material: S.S. 316 Elastic Element: AISI 316 Ti st.st. diaphragm. Accuracy Class: 1.0 as per EN 837-1 Protection Degree: IP65 Model: as below MFR: NUOVAFIMA						
	Accessories 2 Valve Manifold Max Working Pressure: 6000 Psi Material: S.S.316L (NACE MR 0175) Inlet Connection: 1/2" NPTF Outlet Connection: 1/2" NPTF Vent Connection: 1/4" NPTF Model: 2VM01S8FF MFR: VEELOK +Test & Inspection Certificate (for Veelok products)						
Item	Tag No.	Range (Bar)	Type / Model	Manifold	Qty	Delivery	Remark
1	PG-555-004A/B	0-0.6	Diaphragm / MN18	Yes	2	14-16 Working Weeks	
2	PG-555-003A/B	0-60	Bourdon Tube / MGS18	Yes	2	In Stock	
3	PG-555-009A/B	0-0.6	Diaphragm / MN18	Yes	2	14-16 Working Weeks	
4	PG-555-008A/B	0-16	Bourdon Tube / MGS18	Yes	2	In Stock	
5	PG-517-067A/B	0-16	Bourdon Tube / MGS18	Yes	2	In Stock	

Item	Description			
H	Pressure Transmitter			
	Tag No.: as below (SS Tag Plate will be provided as attached picture.)			
	Type: In-Line Pressure Transmitter			
	Range: –14.7 to 150 psi (-1.01 to 10.34 bar)			
	Calibration Range: 0 to 10 Kg/cm2 (g) (for PT-522-307A/B) & 0 to 5 bar (PT-520-303A)			
	Output: 4–20 mA with digital signal based on HART® Protocol			
	Case Material: Stainless Steel			
	Process Connection: 1/2" NPT Female			
	Precess Connection Material: S.S. 316			
	Isolating Diaphragm Material: S.S. 316			
	Sensor Fill Fluid: Silicone			
	Housing Material: Aluminum			
	Electrical Connection: M20 x 1.5 (with Cable Gland)			
	Mounting Bracket: Bracket for 2-in. pipe or panel mounting, all stainless steel			
	Product Certifications: NA			
Display: Yes, LCD display				
Model: 3051TG2A2B21BB4M5				
MFR: ROSEMOUNT				
Accessories				
	Hex Nipple			
	Max Working Pressure: 6000 Psi			
	Material: S.S.316L (NACE MR 0175)			
	Connection: 1/2" NPTM * 1/2" NPTM			
	Model: HN8			
	MFR: VEELOK			
	2 Valve Manifold			
	Max Working Pressure: 6000 Psi			
	Material: S.S.316L (NACE MR 0175)			
	Inlet Connection: 1/2" NPTF			
	Outlet Connection: 1/2" NPTF			
	Vent Connection: 1/4" NPTF			
	Model: 2VM01S8FF			
	MFR: VEELOK			
Item	Tag No.	Qty	Delivery	Remark
1	PT-522-307A/B	2	In Stock	
2	PT-520-303A	1	In Stock	

Item	Description			
J	Differential Pressure Transmitter			
	Tag No.: as below (SS Tag Plate will be provided as attached picture.)			
	Type: Coplanar pressure transmitter ,Differential			
	Range: –300 to 300 psi (–20.68 to 20.68 bar)			
	Calibration Range: 0 to 4 Kg/cm2 (g)			
	Output: 4–20 mA with digital signal based on HART® Protocol			
	Case Material: Stainless Steel			
	O-ring: Glass-filled PTFE			
	Isolating Diaphragm Material: S.S. 316			
	Sensor Fill Fluid: Silicone			
	Housing Material: Aluminum			
	Electrical Connection: M20 x 1.5			
	Mounting Bracket: Coplanar flange bracket, all SST, 2-in. (51 mm) pipe and panel			
	Product Certifications: NA			
	Display: Yes, LCD display			
	Model: 3051CD4A22A1BB4M5			
	MFR: ROSEMOUNT			
Accessories				
	5 Valve Manifold			
	Max Working Pressure: 6000 Psi			
	Material: S.S.316L (NACE MR 0175)			
	Inlet Connection: 2 * 1/2" NPTF			
	Outlet Connection: Suitable For Pressure Transmitter Model 3051			
	Vent Connection: 1/4" NPTF			
	Model: 5VM05S			
	MFR: VEELOK			
Item	Tag No.	Qty	Delivery	Remark
1	PDT-522-301A/B	2	In Stock	

Item	Description			
K	Differential Pressure Transmitter Tag No.: as below (SS Tag Plate will be provided as attached picture.) Type: Coplanar pressure transmitter ,Differential Range: -300 to 300 psi (-20.68 to 20.68 bar) Calibration Range: 0 to 4 Kg/cm2 (g) Output: 4-20 mA with digital signal based on HART® Protocol Case Material: Stainless Steel O-ring: Glass-filled PTFE Isolating Diaphragm Material: S.S. 316 Sensor Fill Fluid: Silicone Housing Material: Aluminum Electrical Connection: M20 x 1.5 Mounting Bracket: Coplanar flange bracket, all SST, 2-in. (51 mm) pipe and panel Product Certifications: ATEX Intrinsic Safety Display: Yes, LCD display Model: 3051CD4A22A1BB4I1M5 MFR: ROSEMOUNT			
	Accessories			
	5 Valve Manifold Max Working Pressure: 6000 Psi Material: S.S.316L (NACE MR 0175) Inlet Connection: 2 * 1/2" NPTF Outlet Connection: Suitable For Pressure Transmitter Model 3051 Vent Connection: 1/4" NPTF Model: 5VM05S MFR: VEELOK			
Item	Tag No.	Qty	Delivery	Remark
1	PDT-522-301A/B	2	In Stock	

Item	Description				
L	Differential Pressure Transmitter Tag No.: as below (SS Tag Plate will be provided as attached picture.) Type: Level transmitter Range: –250 to 250 inH2O (–621.60 to 621.60 mbar) Calibration Range: 0 to 2000 mmWC Output: 4–20 mA with digital signal based on HART® Protocol Process connection: 2-in./DN 50/A, 316L SST, Flush mount only Mounting Flange: 2-in. , ASME B16.5 Class 300 , 316 SST Seal Fill Fluid: Silicone 200 , –49 to 401 °F (–45 to 205 °C) Low Pressure Side: Differential O-ring: Glass-filled PTFE Housing Material: Aluminum Electrical Connection: M20 x 1.5 Product Certifications: NA Display: Yes, LCD display Model: 3051L2AG0YD21ABM5 MFR: ROSEMOUNT				
	Accessories				
	5 Valve Manifold Max Working Pressure: 6000 Psi Material: S.S.316L (NACE MR 0175) Inlet Connection: 2 * 1/2" NPTF Outlet Connection: Suitable For Pressure Transmitter Model 3051 Vent Connection: 1/4" NPTF Model: 5VM05S MFR: VEELOK				
	Item	Tag No.	Qty	Delivery	Remark
	1	LT-522-301A/B	2	In Stock	

Item	Description				
M	Temperature Gauge				
	Tag No.: as below (SS Tag Plate will be provided as attached picture.)				
	Type: Bi-Metal				
	Range: as below				
	Accuracy Class: 1 as per EN 13190, measuring Range				
	Protection Degree: IP65				
	Dial Size: 6"(150mm)				
	Case: Stainless Steel				
	Process Connection: 1/2" NPTF , Every Angle				
	Process Connection Material: S.S.316				
	Stem Diameter: 6mm				
	Stem Length: 200				
	Model: S551				
	MFR: WIKA				
Item	Tag No.	Range (°C)	Qty	Delivery	Remark
1	TG-521-212B, TG-521-213B, TG-521-214B, TG-521-215B	0-200	4	In Stock	

Item	Description				
N	Orifice Plate				
	Tag No.: as below (The tag number and the orientation will be engraved on the handle)				
	Type: Restriction Orifice				
	Orifice Plate Thickness: 3mm				
	Size: 1/2" - #300				
	Material: S.S.316L				
	Bore Diameter: 3.2 mm				
	MFR: ISATIS				
	+ MTC (Material Test Certificate)				
Item	Tag No.	Qty	Delivery	Remark	
1	RO-517-401A/B	2	10 Working Days		
2	RO-517-402A	1	10 Working Days		
3	RO-517-403B	1	10 Working Days		
4	RO-517-404A	1	10 Working Days		
5	RO-517-405A/B	2	10 Working Days		
6	RO-517-401AA/BB	2	10 Working Days		

Item	Description			
E	Level Transmitter Tag No.: as below (The tag number and the orientation will be engraved on the handle) Type: Differential Pressure Calibration Range: 0-2000 mmH2O Output signal: 4 to 20 mA DC with digital communication (HART 5/HART 7 protocol) Measurement span (capsule): 1 to 100 kPa (4 to 400 inH2O) Process connections: 1/4 NPT female on the cover flanges (Coupled to Diaphragm Seal) Bolts and nuts material: 316L SST Installation: Horizontal piping and left side high pressure Amplifier housing: Cast aluminum alloy Fill Fluid: Silicone Diaphragm Material: Hastelloy C-276 Electrical connection: M20*1.5 female, two electrical connections Integral indicator: Digital indicator with the range setting switch (push button) Mounting bracket: 304 SST 2-inch pipe mounting, flat type (for horizontal piping) Ambient Temperature Effects per 28°C (50°F) Change: ±(0.07% Span + 0.02% URL) Process Temperature Limits -40 to 120°C (-40 to 248°F Cover O-ring: Buna-N Approval: Multiple types of protection (KF22, KS21 (II 1 G Ex ia IIC T4 Ga, II 2 D Ex ia IIIC T85°C T100°C T120°C Db) or Intrinsically safe Ex ic) Applicable Standard: EN IEC 60079-0, EN 60079-11 II 3 G Ex ic IIC T4 Gc, Amb. Temp.: -30 to 60°C (-22 to 140°F) Ui=30 V, Ci=27.6 nF, Li=0 µH Degrees of Protection: IP66/IP67 Power Supply: 10.5 to 32 V DC External Zero Adjustment: Yes Failure Alarm: Yes Model: EJA110E-JMS5G-914EB/KU22 MFR:Yokogawa			
	Accessories Diaphragm Seal With Capillary (2 Sets for High and low sides) Type: Flanged, Flushed Type, Remote with Capillary Fill Fluid: Silicone Body Material: S.S.316L Diaphragm Material: S.S.316L Process Connection: 2" 150# RF , ASME B16.5 Capillary Length: 6 m for each leg Capillary Material: S.S.316+ PVC armor MFR: ISATIS			
Item	Tag No.	Qty	Delivery	Remark
E-1	LZT-526-083	1	10 Working Days	

Item	Description								
F	Pressure Gauge								
	Tag No.: as below (SS Tag Plate will be provided.)								
	Type: Solid Front , Bourdon Tube (seamless tube: AISI 316L st.st)								
	Range: as below								
	Dial Size: 150 mm								
	Dial: Aluminium, White with Black Markings								
	Movement: Stainless Steel with Internal Limit Stops								
	Socket Material: AISI 316L st.st.								
	Case, Ring and Blow-out Disk: AISI316L st.st								
	Process Connection: 1/2" NPTM , Bottom								
	Precess Connection Material: S.S. 316								
	Accuracy Class: 1 as per EN 837-1								
	Protection Degree: IP65								
	Pointer: Adjustable								
	Model: MGS20								
	MFR: NUOVAFIMA								
Accessories									
	Diaphragm Seal								
	Type: Threaded , Direct , Flush								
	Body Material: S.S.316								
	Fill Fluid: Silicone								
	Diaphragm Material: S.S.316								
	Process Connection: 1/2" NPT Male								
	Gauge Connection: 1/2" NPT Female								
	MFR: ISATIS								
	Pressure Gauge Snubber (PGS)					Adjustable Overload Protector (AOP)			
	Max. Working Pressure: 6000 psi					Max. Working Pressure: 6000 psi			
	Material : S.S.316L (NACE MR 075)					Material : S.S.316L (NACE MR 075)			
	Inlet Connection: 1/2" NPT Male					Inlet Connection: 1/2" NPT Male			
	Outlet Connection: 1/2" NPT Female					Outlet Connection: 1/2" NPT Female			
	Model : PGSS8MF					Setting Range: 2~60 bar			
MFR: Veelok					Model : AOP				
					MFR: Veelok				
Item	Tag no.	Range (bar)	Accessories				Qty	Delivery	Remarks
			PGS	AOP	Glycerine	Diaphragm Seal			
F-1	PG-526-121	0-2.5	No	Yes	Yes	Yes	1	14-16 Working Weeks	
F-2	PG-526-120	0-4	Yes	Yes	Yes	Yes	1	14-16 Working Weeks	

Item	Description			
G	Flow Transmitter Tag No.: as below (The tag number and the orientation will be engraved on the handle) Type: Differential Pressure Calibration Range: 0-2000 mmH2O Output signal: 4 to 20 mA DC with digital communication (HART 5/HART 7 protocol) Measurement span (capsule): 1 to 100 kPa (4 to 400 inH2O) Process connections: 1/4 NPT female on the cover flanges (Coupled to Diaphragm Seal) Bolts and nuts material: 316L SST Installation: Horizontal piping and left side high pressure Amplifier housing: Cast aluminum alloy Fill Fluid: Silicone Diaphragm Material: Hastelloy C-276 Electrical connection: M20*1.5 female, two electrical connections Integral indicator: Digital indicator with the range setting switch (push button) Mounting bracket: 304 SST 2-inch pipe mounting, flat type (for horizontal piping) Ambient Temperature Effects per 28°C (50°F) Change: ±(0.07% Span + 0.02% URL) Process Temperature Limits -40 to 120°C (-40 to 248°F) Cover O-ring: Buna-N Approval: Multiple types of protection (KF22, KS21 (II 1 G Ex ia IIC T4 Ga, II 2 D Ex ia IIIC T85°C T100°C T120°C Db) or Intrinsically safe Ex ic) Applicable Standard: EN IEC 60079-0, EN 60079-11 II 3 G Ex ic IIC T4 Gc, Amb. Temp.: -30 to 60°C (-22 to 140°F) Ui=30 V, Ci=27.6 nF, Li=0 µH Degrees of Protection: IP66/IP67 Power Supply: 10.5 to 32 V DC External Zero Adjustment: Yes Failure Alarm: Yes Model: EJA110E-JMS5G-914EB/KU22 MFR:Yokogawa +Calibration Certificate			
	Accessories			
	Manifold Type: 3 Valve Material: S.S.316L (NACE MR0175) Max Working Pressure: 6000 psi Inlet Connection: 1/2" NPT Female Outlet Connection: Flange Vent Connection: 1/4" NPT Female Model: 3VM03S MFR:Veelok	Orifice Plate Size: 1 1/2" 300# Type: Square Edge & Concentric Orifice Facing: Raised Material: SS316 Plate Thickness: 3 mm Bore Diameter: will be calculated after PO Vent Hole Diameter(mm): will be calculated after PO MFR: Isatis	Orifice Flange Type: Weld Neck Material: ASTM A105 Size: 1-1/2" #300 RF , ASME B16.36 Tap Size: 2 * 1/4" NPT Female MFR: FAD or Equivalent	
	Gasket Material Size: Acc. to size of Flanges Type: Spiral Wound Material: SS304 + Graphite Filler , ASME B16.20 MFR: Behta Flange Stud Bolt and Hex Nuts (Material: Stud Bolts to ASTM A193 GR.B7, Nuts to ASTM A194 GR.2H)			
Item	Tag No.	Qty	Delivery	Remark
G-1	FT-517-070	1	10 Working Days	

شرایط:

برای اقام فوق گواهی کالیبراسیون و گواهی اصالت (نسخه الکترونیکی) ارائه میگردد.

تحويل: انبار شرکت ایساتیس فرایند ابزار

اقلام موجود بر اساس موجودی روز انبار می باشد و هنگام ثبت سفارش نیاز به استعلام مجدد خواهد بود.

مهندس فروش: فرناز سوری Tel: +98 21 88480795 & 7 Ext: 216